

PP/PCW REGRIND

SPECIFICATIONS

- **PURITY OF THE MATERIALS**

Our flakes meets a purity of 95% PP
(only some PE content is present)

- **ORIGIN OF THE MATERIALS**

Post Consumers Packaging Waste.

- **TRUCK WEIGHT**

On average 19,5 Ton.

- **MELT FLOW INDEX**

About MFI 10-15 (2,16 kg / 230)

- **COLOUR**

Mixed colours

PP/PCW REGRIND AUFDERHAAR KUNSTSTOF RECYCLING B.V.

Our PP/PCW regrind is processed from Post Consumer Packaging Waste and has mixed colours. After pre-sorting and removing visual contaminations, our washing lines clean out the organics and separate the flakes by a sink-flow process. The PP/PCW regrind Aufderhaar supplies is best used for extrusion and compounding. Our PP/PCW regrind is packed in big-bags which makes it possible us to load shipping containers or semitrailers. Even shipping in a bulk trailer is possible.

Aufderhaar Kunststof Recycling B.V. is a family owned company which produces between 150 to 200 Tons of high quality regrind every week. To make sure our quality meets the costumers requirements we do a check on each big-bag.

With 5 washing lines we are able to respond most recycling situations. Even toll work is a possibility to get your material (PP, HDPE or PS) processed to flakes.